

Material Safety Data Sheet

May be used to comply with
OSHA's Hazard Communication Standard
29 CFR 1910.1200. Standard must be
consulted for specific requirements

U.S. Department of Labor

Occupation Safety and Health Administration
(Non-Mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY LEMON SHEEN (120245)	<i>Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.</i>
---	--

Section I	D.O.T. Hazard Class: Consumer Commodity ORM-D
------------------	---

Manufactured For: Beaver Research Company	Emergency Telephone Number 1-800-255-3924 (Chem-Tel)
Address (Number, Street, City, State, and ZIP Code) 3700 E. Kilgore Road, Portage, MI 49002	Telephone Number For Information 1-800-544-0133
HMIS RATINGS: 0=Minimal 3=Serious 1=Slight 4=Extreme 2=Moderate	Health: 1 Fire: 1 Reactivity: 0 Personal Protection: B
	Date Prepared 11/15/07
	Signature of Preparer (optional)

Section II - Hazardous Ingredients/Identity Information
--

Hazardous Components (Specific Chemical Identity; Common Name(s))	CAS No.	PEL	TWATLV	Carcinogen	% WT
Mineral Oil	8042-47-5	5 mg/m ³ *	5 mg/m ³ *	No	5-15
Liquified Petroleum Gas	68476-86-8	1000 ppm	1000 ppm	No	10-20

* exposure limits for mist

Section III - Physical/Chemical Characteristics
--

Boiling Point	>200°F	Specific Gravity (H ₂ O = 1) @ 75°F	0.973
Vapor Pressure (can; psig @ 72°F)	50	Melting Point	N/A
Vapor Density (AIR = 1)	>1	Total VOC (Volatile Organic Compound)	16.02%
Solubility in Water	pH		
Emulsifies	7.13		
Appearance and Odor	Viscous, white liquid with lemon odor.		

Section IV - Fire and Explosion Hazard Data
--

Flash Point (Method Used) None to Boiling	Flammable Limits Non-Flammable Spray	LEL N/A	UEL N/A
Extinguishing Media Foam, CO ₂ , Dry Media	Special Fire Fighting Procedures Wear self-contained breathing apparatus and protective clothing. Cool fire exposed containers to prevent rupturing.		
Unusual Fire and Explosion Hazards Exposure to temperature above 120°F may cause bursting.			

Section V - Reactivity Data

Stability	Unstable	Conditions to Avoid	N/A
	Stable	X	
Incompatibility (Materials to Avoid) Avoid contact with strong oxidizing agents.	Hazardous Decomposition or Byproducts Carbon Dioxide, Carbon Monoxides		
Hazardous Polymerization	May Occur	Conditions to Avoid	N/A
	Will Not Occur	X	

Section VI - Health Hazard Data

Route(s) of Entry:	Inhalation?	Skin?	Eyes?	Ingestion?
	Yes	Yes	Yes	Yes

Health Hazards (Acute and Chronic)

Eyes: May cause irritation accompanied by redness, tearing and blurred vision. **Skin:** Prolonged or repeated contact with skin can cause defatting and drying of the skin resulting in skin irritation and dermatitis. **Inhalation:** Breathing excess vapor or mist may cause irritation of respiratory tract. Prolonged or abusive exposure can cause headache, dizziness, rapid breathing, anesthesia, drowsiness, unconsciousness and other central nervous system effects, possibly including death. **Ingestion:** May cause gastrointestinal irritation and diarrhea. Aspiration of material into the lungs can cause pulmonary injury, possibly progressing to death.

Carcinogenicity:	NTP?	IARC Monographs?	OSHA Regulated?
	No	No	No

Signs and Symptoms of Exposure

See above "Health Hazards".

Medical Conditions Generally Aggravated by Exposure

May aggravate existing skin conditions, eye and respiratory disorders.

Emergency and First Aid Procedure

Eyes: Flush with large amounts of cool running water for at least 15 minutes while holding upper and lower lids open. If irritation persists get medical attention immediately. **Skin:** Wash with soap and water. If irritation persists, seek medical attention. **Inhalation:** Remove to fresh air. Seek medical attention immediately. If breathing stops give artificial respiration. **Ingestion:** Do not induce vomiting. Seek medical attention immediately.

Section VII - Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled

Allow propellant to evaporate. Maintain local exhaust and adequate ventilation. No smoking. Keep sparks, heat sources and open flame far away from spill or leak. Cover with absorbent material and sweep up. Wash area to prevent slipping. Dispose of soaked absorbent material in accordance with Federal, State and local laws.

Waste Disposal Method

Aerosol cans, when emptied and depressurized through normal use, pose no disposal hazard and should be recycled. Consult Federal, State and local authorities for approved procedures.

Precautions to be Taken in Handling and Storage

For Industrial and Institutional use only. Store in a cool, dry area away from heat or open flame. Do not store at temperatures above 120°F. **NFPA Code 30B Rating:** Level 1 Aerosol.

Other Precautions

Keep out of reach of children.

Section VIII - Control Measures

Respiratory Protection (Specify Type)

None needed for proper use in accordance with label directions.

Ventilation	Local Exhaust	Yes	Special	N/A
	Mechanical(General)	N/A	Other	N/A

Protective Gloves

Use chemical resistant gloves if hand contact will be made.

Eye Protection

Always wear safety glasses or chemical proof goggles when working with chemicals.

Other Protective Clothing or Equipment

N/A

Work/Hygienic Practices

N/A

N/A=Not Applicable N/E=Not Established N/D=Not Determined <=Less Than >=More Than

The information contained on this Material Safety Data Sheet is considered accurate as of the date of publication. It is not necessarily all inclusive nor fully adequate in every circumstance. The suggestions should not be confused with, nor followed in violation of applicable laws, regulations rules or insurance requirements. No warranty, express or implied, of merchantability, fitness, accuracy of data, or the results to be obtained from the use thereof is made. The vendor assumes no responsibility for injury or damages resulting from the inappropriate use of this product.